



SUSPENSION SETUP GUIDE

Bike	Top Fuel 9.9, 9.8				Top Fuel 9.7				Top Fuel 9				Top Fuel 8				
Travel	100mm				100mm				100mm				100mm				
Shock stroke	36mm				36mm				36mm				36mm				
Shock Sag %	20-25% - sitting on bike				20-25% - sitting on bike				20-25% - sitting on bike				20-25% - sitting on bike				
Fork Sag %	20-25% - standing on bike				20-25% - standing on bike				20-25% - standing on bike				20-25% - standing on bike				
Suspension	Front 9.9 — 32 F-Series Remote FIT 9.8 — 32 F-Series Remote		Rear RP23 Boost Valve		Front Rockshox SID RLT		Rear RP2		Front 32-F-Series Remote		Rear RP2		Front Reba SL			Rear Float RP-2	
	Rider Weight (lbs)	Spring (PSI)	Reb (clicks out)	Spring (PSI)	Reb (clicks out)	Spring (PSI)	Reb (clicks out)	Spring (PSI)	Reb (clicks out)	Spring (PSI)	Reb (clicks out)	Spring (PSI)	Reb (clicks out)	Positive Air Spring	Negative Air Spring	Reb (clicks out)	Spring (PSI)
100	50	14	108	7	70	12	108	7	50	14	108	7	70	70	12	108	7
110	55	14	115	7	75	12	115	7	55	14	115	7	75	75	12	115	7
120	60	12	122	6	80	12	122	6	60	12	122	6	80	80	12	122	6
130	60	12	128	6	85	11	128	6	60	12	128	6	85	85	11	128	6
140	65	11	135	6	90	11	135	6	65	11	135	6	90	90	11	135	6
150	65	11	142	5	95	11	142	5	65	11	142	5	95	95	11	142	5
160	70	10	148	5	100	10	148	5	70	10	148	5	100	100	10	148	5
170	70	10	155	5	105	10	155	5	70	10	155	5	105	105	10	155	5
180	75	9	162	4	110	10	162	4	75	9	162	4	110	110	10	162	4
190	75	9	168	4	115	9	168	4	75	9	168	4	115	115	9	168	4
200	80	8	175	4	120	9	175	4	80	8	175	4	120	120	9	175	4
210	80	8	182	3	125	9	182	3	80	8	182	3	125	125	9	182	3
220	85	7	195	3	130	8	195	3	85	7	195	3	130	130	8	195	3
230	85	7	208	3	135	8	208	3	85	7	208	3	135	135	8	208	3
240	90	6	222	2	140	7	222	2	90	6	222	2	140	140	7	222	2
250	100	6	242	2	145	7	242	2	100	6	242	2	145	145	7	242	2



SUSPENSION SETUP GUIDE

Follow these steps to optimize the performance of your Trek Full Suspension Mountain Bike:

1. Determine rider weight (individual weight plus riding gear).
2. Adjust rebound and low speed compression settings if applicable as indicated in chart. Turn Pro Pedal off. (If adjusting a Top Fuel 9.8 or 9.9, be sure Pro Pedal is off and is in the 1 setting.)
3. Be sure to thread the pump head completely on to the valve. Apply pressure as indicated in the chart. Remove pump.
4. Install Trek Sag Meter. If you cannot locate your sag meter, skip ahead to step 6.
5. If adjusting fork, stand on the pedals. If adjusting shock, remain seated.
6. Slide O-ring so that it rests against dust seal.
7. Dismount bike.
8. If o-ring falls within sag meter's window, or if o-ring is within recommended sag measurement, you're ready to ride.
9. If the o-ring falls outside of that window, or is greater or less than recommended measurement, add or subtract pressure as needed.